



NW 65

ABRASIVE POLISH



PRODUCT DESCRIPTION

Abrasive polish for the refinishing process of resins and composite materials, used to remove minor scratches and small defects as well as swirl marks, which may come from previous coarse compounds. Through its combination of micro-abrasives and glossifiers, it has an excellent refinishing action on plugs and moulds. It can be used also as extra fine paste for removing light oxidation or for the last step on washbasins and shower trays, providing a remarkable deep shine.

PHYSICAL PROPERTIES

Colour: White
Physical form: Liquid-creamy
Odour: Light and pleasant
Density: 1,290 g/ml
Flammability: Not flammable
Type of surface: Gelcoat

HOW TO USE

Shake before use, then apply by variable speed polisher, selecting an anti-scratch wool pad **SL3**. Pour a small quantity of compound on the polisher-pad. Let the polisher turn at low revolutions, speeding them up (1000-2000 RPM) while spreading the paste with crossed movements. Keep polishing until you reach a very bright surface, always paying attention at not overheating the surface. Eventually, wipe it off with a clean cloth.

PRODUCT INFORMATION

Packaging	Code	Pcs/Box
1 kg	600035	12
5 kg	PBNW6500P0GB	2

INSTRUCTIONS FOR USE




P2000-P2500



SL3 WOOL



**RPM
800-1500**



CROSSED MOVEMENTS

RECOMMENDATIONS



SHAKE BEFORE USE



APPLY SMALL QUANTITY



**MEDIUM SOFT
FOAM**

AS AN ALTERNATIVE TO
WOOL



5-35°

STORAGE

PREVIOUS STEPS



NW 0



ST1 WOOL

