




I-CUT

HIGH CUTTING COMPOUND



PRODUCT DESCRIPTION

This is a very cutting liquid compound used to remove marks, failings, dullness and P1200-P2000 sand scratches, according to the hardness of treated paints. It may be used both on oxidized surfaces and new well dried paints.

PHYSICAL PROPERTIES

Colour: White
Physical form: Creamy
Odour: Light and pleasant
Density : 1,570 g/ml
Flammability: Not flammable
Type of surface: Car bodywork



HOW TO USE

Please apply a small quantity of compound on a hard-white foam pad. Let the polisher turn at low revolutions, speeding them up (800-1500 RPM) while spreading the paste with crossed movements. Pay attention at not overheating the paint. If necessary, please repeat the application more times till the complete cancellation of scratches. Eventually, wipe the surface with a clean Silky Microfiber towel. For a better finishing, we suggest to end the treatment with a finer compound.

PRODUCT INFORMATION

Packaging	Code	Pcs/Box
0,5 kg	600207	20
1 kg	600220	12
5 kg	600196	2
Packaging	Black Code	Pcs/box
0,5 kg	600208	20
1 kg	600219	12
5 kg	600195	2

INSTRUCTIONS FOR USE



CROSSED MOVEMENTS

RECOMMENDATIONS




SHAKE BEFORE USE



APPLY SMALL QUANTITY



AS AN ALTERNATIVE TO FOAM





STORAGE


FOLLOWING STEPS



IPER-CUT 1



SUPERFINISHER 2



SIRIUS

