



2 FINISHING

3 PROTECTION

UNIQA

ROTORBITAL ONE STEP





PRODUCT DESCRIPTION

One step polishing compound specific for rotorbital machine. Thanks to the innovative mix of abrasives it removes marks, failing, dullness and P1500-P3000 sand scratches, according to the hardness of treated paints. It may be used both on oxidized surfaces and new well dried paints. It can be used both on oxidized paints and on fresh, well-dried supports.

PHYSICAL PROPERTIES

Colour: White
Physical form: Creamy
Odour: Light and pleasant
Density: 1,070 g/ml

Flammability: Not flammable Type of surface: Car bodywork

HOW TO USE

Please apply a small quantity of compound on a medium-hard orange foam pad. Let the polisher turn at low revolutions, speeding them up (800-1500 RPM) while spreading the paste with crossed movements. Pay attention at not overheating the paint. Do not overstay on the surface without adding more product. If necessary, please repeat the application more times till the complete removal of scratches. Eventually, wipe the surface with a Silky Microfiber towel.

PRODUCT INFORMATION

Packaging	Code	Pcs/Box
0,5 kg	600621	20
1 kg	600620	12

INSTRUCTIONS FOR USE









CROSSED MOVEMENTS

RECOMMENDATIONS








APPLY SMALL QUANTITY



AS AN ALTERNATIVE TO **FOAM**



STORAGE

FOLLOWING STEPS







