




HEAVY CUT

► **MEDIUM CUT**

FINISH

SUPER FINISH



- **Level of cut:** 9
- **Level of gloss:** 9
- **Colour:** white
- **Odour:** light and pleasant
- **Physical form:** creamy
- **Storage:** 5-30°C

CODES

Code	Size	Pcs/Box
(EU) 600712	250 g	24
(EU) 600708	1 kg	12
(US) 600694	8 oz	24
(US) 600690	32 oz	12

PRODUCT DESCRIPTION

Highly efficient water based and silicon free cutting-polishing compound used to remove P1500-P3000 sand scratches, as well as deep marks, failings and dullness, according to the hardness of treated paints. It restores oxidized surfaces, as well as can be used on new well dried paints.

The key feature of PAICAR 02 is offering a perfectly balanced action: the high cutting power does not compromise the high level of gloss that can be achieved: fast cut and glossy finishing coexist, and this is the reason why it is considered a one-step compound.

PAICAR 02 has been developed to give its best in combination with a rotorbital polishing machine and DA-02 orange medium-hard foam pad. It may be used also in combination with SL3 lamb wool pad and a rotary machine, for higher cutting action.

HOW TO USE

Apply a small quantity of PAICAR 02 on DA-02 orange foam pad and use the pad for spreading the compound on the surface. Select a rotorbital polisher and start at low RPM, then gradually increase revolutions and polish with crossed movements, namely left to right, up and down. Wipe the surface with a clean Silky Tech microfiber cloth, in order to remove any potential residue. Follow the same procedure when using SL3 lamb pad, selecting a rotary polishing machine: start slow (800 RPM), increase gradually to 2000 RPM.

TIPS

- Clean surface thoroughly before polishing
- Shake well before use
- Apply a small amount of compound
- Polish with crossed movements: left to right, up and down
- Use rotary polisher for powering the cut level
- Use DA-01 Red hard polishing pad for standard condition
- Keep the polishing pad clean to speed up polishing process and maximise pad life
- Use SL3 lamb wool for badly oxidized surfaces
- Use a clean Silky Tech microfiber to wipe off without too much pressure